

CLAIMS

I claim:

- 1 1. A mechanic's creeper, comprising:
 - 2 a hollow tubular main frame having at least a left side
 - 3 member, a right side member, and a head crossmember;
 - 4 a frame extension having at least a left side member, a
 - 5 right side member, and a foot crossmember, with the left side
 - 6 member and the right side member of said frame extension
 - 7 telescopingly disposed respectively within the left side member
 - 8 and the right side member of said main frame;
 - 9 a back rest pad secured to said main frame;
 - 10 a buttocks support cushion removably attached to said frame
 - 11 extension;
 - 12 a left and a right head end wheel depending from said main
 - 13 frame, near said head crossmember thereof; and
 - 14 a left and a right foot end wheel depending from said frame
 - 15 extension adjacent said foot crossmember thereof.

- 1 2. The mechanic's creeper according to claim 1, further
 - 2 including a tool and equipment storage compartment disposed
 - 3 between said left side member and said right side member of said
 - 4 main frame, and below said back rest pad.

1 3. The mechanic's creeper according to claim 1, further
2 including a storage and carrying case therefor.

1 4. The mechanic's creeper according to claim 1, further
2 including a left and a right arm rest removably attached
3 respectively to said left side member and said right side member
4 of said main frame.

1 5. The mechanic's creeper according to claim 4, further
2 including a tool storage pouch foldably depending from each said
3 arm rest.

1 6. The mechanic's creeper according to claim 1, further
2 including at least one adjustably positionable work light
3 extending from said main frame adjacent said head crossmember
4 thereof.

1 7. The mechanic's creeper according to claim 1, further
2 including a warning light removably attached to said main frame.

1 8. A mechanic's creeper, comprising:
2 a hollow tubular frame assembly having at least a left side
3 member, a right side member, a head crossmember, and a foot
4 crossmember;
5 a tool and equipment storage compartment disposed between
6 the left side member and the right side member of said frame
7 assembly;
8 a back rest pad hingedly secured to one of the side members
9 of said frame assembly and over said tool and equipment storage
10 compartment; and
11 a left and a right head end wheel, and a left and a right
12 foot end wheel, the wheels depending from said frame assembly.

1 9. The mechanic's creeper according to claim 8, wherein
2 said frame assembly comprises:

3 a hollow tubular main frame having at least a left side
4 member, a right side member, and a head crossmember;

5 a frame extension having at least a left side member, a
6 right side member, and a foot crossmember, with the left side
7 member and the right side member of said frame extension
8 telescopingly disposed respectively within the left side member
9 and the right side member of said main frame; and

10 a buttocks support cushion removably attached to said frame
11 extension.

1 10. The mechanic's creeper according to claim 8, further
2 including a storage and carrying case therefor.

1 11. The mechanic's creeper according to claim 8, further
2 including a left and a right arm rest removably attached
3 respectively to said left side member and said right side member
4 of said frame assembly.

1 12. The mechanic's creeper according to claim 11, further
2 including a tool storage pouch foldably depending from each said
3 arm rest.

1 13. The mechanic's creeper according to claim 8, further
2 including at least one adjustably positionable work light
3 extending from said frame assembly adjacent said head
4 crossmember thereof.

1 14. The mechanic's creeper according to claim 8, further
2 including a warning light removably attached to said frame
3 assembly.

1 15. A mechanic's creeper, comprising:

2 a hollow tubular frame assembly having at least a left side
3 member, a right side member, a head crossmember, and a foot
4 crossmember;

5 a back rest pad secured to said main frame;

6 a left and a right head end wheel, and a left and a right
7 foot end wheel, the wheels depending from said frame assembly;
8 and

9 a storage and carrying case configured for storing and
10 carrying therein, at least said frame assembly including said
11 back rest pad and each said wheel.

1 16. The mechanic's creeper according to claim 15, wherein
2 said frame assembly comprises:

3 a hollow tubular main frame having at least a left side
4 member, a right side member, and a head crossmember;

5 a frame extension having at least a left side member, a
6 right side member, and a foot crossmember, with the left side
7 member and the right side member of said frame extension
8 telescopingly disposed respectively within the left side member
9 and the right side member of said main frame; and

10 a buttocks support cushion removably attached to said frame
11 extension.

1 17. The mechanic's creeper according to claim 15, further
2 including a tool and equipment storage compartment disposed
3 between said left side member and said right side member of said
4 frame assembly, and below said back rest pad.

1 18. The mechanic's creeper according to claim 15, further
2 including a left and a right arm rest removably attached
3 respectively to said left side member and said right side member
4 of said frame assembly.

1 19. The mechanic's creeper according to claim 18, further
2 including a tool storage pouch foldably depending from each said
3 arm rest.

1 20. The mechanic's creeper according to claim 15, further
2 including:

3 at least one adjustably positionable work light extending
4 from said frame assembly adjacent said head crossmember thereof;
5 and

6 a warning light removably attached to said frame assembly.